

Pillow Pack





Main Data

Output

- Up to 2000 pcs/min

Size Range

- Length: 10-40 mm - Width: 10-40 mm - Height: 5-25 mm Special sizes upon request

Connected Load

- 9 kw

Utilities

- Compressed air consumption: 4 l/min
- Compressed air pressure: 0.4-0.6 MPa

Wrapping Materials

- Heat sealable foil
- PP film

Wrapping Material Dimensions

- Reel diameter: max. 330 mm - Reel width: 60-100 mm

- Core diameter: 76 mm

Machine Measurements

- Length: 3390 mm - Width: 1390 mm - Height: 1670 mm

Machine Weight

- 2500 kg

BFK2000A

PILLOW PACK **MACHINE**

BFK2000A pillow pack machine is an excellent wrapping solution for hard candies, toffees, dragee pellets, chocolates, bubble gums, jellies, and other preformed candy products. BFK2000A is equipped with 5 servo motors, 4 converter motors, ELAU motion controller and HMI system

Special Features

- 0% empty bags in finished products
- 0% adhesive bags in finished products
- Independent servo driven for feeding disc and distribution disc
- Servo driven for feeding chain
- Servo driven for longitudinal sealer
- Servo driven for horizontal sealer
- Servo driven for a pair of feeding rollers
- Pneumatic locking device for film core
- Assistant film pulling device
- Centralized lubrication

Chengdu SANKE Industry Co., Ltd.

Add: No.518 Baiyun Road, Eastern Industrial Zone, Xindu District, Chengdu City, P.R. China / Postcode: 610500

Phone: +86 28 8396 4810 / Fax: +86 28 8396 4252

Website: www.san-ke.com / Facebook: www.facebook.com/SankePacking

