



Main Data

Output

- 700-800 pcs/min

Size Range

- Ball dia. Φ : 20-38 mm
- Bar dia. Φ : 3.0-6.5 mm
- Total length: 75-130 mm

Connected Load

- 16.7 kw

Utilities

- Dry compressed air consumption: 3 m³/h
- Compressed air pressure: 400-600 kPa
- Circulating soft water for induction heater: 15-20°C

Wrapping Materials

- Cellophane
- Polyurethane
- Heat sealable foil

Wrapping Material Dimensions

- Width: 74-130 mm
- Core dia.: 76 mm

Machine Measurement

- Length: 2700 mm
- Width: 2000 mm
- Height: 1800 mm

Machine Weight

- 2500 kg

Special Features

- PLC Motion control system, Touch screen HMI, Integrated control
- Servo wrapping materials feeding and cutting, positioned wrap
- No product, no wrapping materials and door open machine stops
- Film antistatic device
- Two systems for twist heating seal device: high frequency electromagnetic induction heater, LEISTER air conduction heater
- Modularity design, easy for maintenance and clean
- CE certification

BNS800

BALL-SHAPED LOLLIPOP DOUBLE TWIST WRAPPING MACHINE

BNS800 ball-shaped lollipop double twist wrapping machine is designed to wrap ball-shaped lollipops in double twist style

Chengdu SANKE Industry Co., Ltd.

Add: No.518 Baiyun Road, Eastern Industrial Zone, Xindu District, Chengdu City, P.R. China / Postcode: 610500

Phone: +86 28 8396 4810 / Fax: +86 28 8396 4252

Website: www.san-ke.com / Facebook: www.facebook.com/SankePacking

We reserve the right to change any or all specifications without prior notice

