



Pillow Pack



Main Data

Output

- Up to 2000 pcs/min

Size Range

- Length: 10-40 mm
- Width: 10-40 mm
- Height: 5-25 mm
Special sizes upon request

Connected Load

- 9 kw

Utilities

- Compressed air consumption: 4 l/min
- Compressed air pressure: 0.4-0.6 MPa

Wrapping Materials

- Heat sealable foil
- PP film

Wrapping Material Dimensions

- Reel diameter: max. 330 mm
- Reel width: 60-100 mm
- Core diameter: 76 mm

Machine Measurements

- Length: 3390 mm
- Width: 1390 mm
- Height: 1670 mm

Machine Weight

- 2500 kg

BFK2000A

PILLOW PACK MACHINE

BFK2000A pillow pack machine is an excellent wrapping solution for hard candies, toffees, dragee pellets, chocolates, bubble gums, jellies, and other preformed candy products. BFK2000A is equipped with 5 servo motors, 4 converter motors, ELAU motion controller and HMI system

Special Features

- 0% empty bags in finished products
- 0% adhesive bags in finished products
- Independent servo driven for feeding disc and distribution disc
- Servo driven for feeding chain
- Servo driven for longitudinal sealer
- Servo driven for horizontal sealer
- Servo driven for a pair of feeding rollers
- Pneumatic locking device for film core
- Assistant film pulling device
- Centralized lubrication

Chengdu SANKE Industry Co., Ltd.

Add: No.518 Baiyun Road Eastern Industrial Zone, Xindu District, Chengdu City, P.R. China / Postcode: 610500

Phone: +86 28 8396 4810 / Fax: +86 28 8396 4252

Website: www.san-ke.com / Facebook: www.facebook.com/SankePacking

We reserve the right to change any or all specifications without prior notice



Official Wechat