



ULD

COOLING TUNNEL

ULD series cooling tunnel is the cooling equipment for candy production. The conveyor belts in cooling tunnel are driven by SEW motor with reducer. Speed adjustment via Siemens frequency converter, cooling system equipped with BITZER Compressor, Emerson electronic expansion valve, Siemens proportion triple valve, KÜBA cool air blower, surface cooler device, temperature and RH adjustable via PLC control system and touch screen HMI

Special Features

- Antilock escape device in cooling tunnel
- 80mm polyurethane-filled wall
- Modular design, integrated control, easy to maintain and clean
- CE certification

Combinations

- ULD can be combined with SANKE's TRCJ extruder, UJB mixer, TRCY, BZK, wrapping machines SK-1000-I, BZW1000 and BZH for different candy production lines

Main Data

Speed of Conveyor Belt Line

- 10-40 meters/min

Connected Load

- 25-45 kw

Utilities

- Water temperature: 15-20 °C
- Water pressure: 0.3-0.4 MPa

Chengdu SANKE Industry Co., Ltd.

Add: No.518 Baiyun Road, Eastern Industrial Zone, Xindu District, Chengdu City, P.R. China / Postcode: 610500

Phone: +86 28 8396 4810 / Fax: +86 28 8396 4252

Website: www.san-ke.com / Facebook: www.facebook.com/SankePacking

We reserve the right to change any or all specifications without prior notice

